

Soft-faced Hammer Safety medium soft/very hard, Ø 50 mm, 360 mm with hickory handle - Wiha 26659

Item no. WH-26659

Manufacturer Wiha

EAN 4010995266592

The Wiha Safety soft-faced hammer 832-39 with 50 mm round face combines a medium-soft (black) and a very hard (white) face on a hickory handle for recoilless blows across construction and industry applications. GS tested, overall length 360 mm.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Poland
HS-Code	82052000
Weight	1.099 kg



DESCRIPTION

The Wiha Safety soft-faced hammer 832-39 with 50 mm hammer face offers two hardness levels for applications ranging from drywall to heavy industry. The recoiling impact effect reduces effort, while the safety faces protect the workpiece material from damage.

BENEFITS

- Recoiling impact effect - less effort required during repeated blows
- Very hard white face (Ø 50 mm) for heavy industry, construction, foundries, and road building
- Medium-soft black face (Ø 50 mm) for paving, tiling, and drywall construction
- Safety faces reliably protect the processed material from damage
- Hickory wooden handle with effective non-slip grip - handle and faces available as spare parts

TECHNICAL DATA

- Diameter hammer face: 50 mm
- Overall length: 360 mm
- Hammer head height: 131 mm
- Dimensions: 360 x 131 x 57 mm (L x W x D)

APPLICATIONS

Very hard face for heavy industry, construction, foundries, and road building. Medium-soft face for paving, tiling, and drywall. Made in Poland, HS 82052000. GS tested.