

Soft-faced Hammer Safety 60 mm Medium Soft/Hard with Hickory Handle - Wiha 26614

Item no. WH-26614

Manufacturer Wiha

EAN 4010995266141

The Wiha Safety soft-faced hammer 60 mm combines two interchangeable 60 mm round faces - medium-soft black and hard orange - on a hickory handle with 400 mm overall length. It handles paving, tiling, drywall construction and assembly or dismantling work.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Poland
HS-Code	82052000
Weight	1.64 kg



DESCRIPTION

The Wiha Safety soft-faced hammer 60 mm delivers recoilless positioning blows that protect delicate surfaces and edges. The approx. 25 % greater head mass provides optimum impact power with reduced effort. The black medium-soft face (60 mm) suits paving, tiling and drywall work; the orange hard face tackles assembly, dismantling and building-site or workshop tasks.

BENEFITS

- Recoilless operation protects joints and delicate workpiece surfaces
- Approx. 25 % greater head mass for optimum impact with less effort
- Two hardness grades: medium soft (black) and hard (orange), 60 mm diameter each
- High-grade hickory handle with non-slip surface, 400 mm overall length
- Hammer faces and handle available separately as spare parts

TECHNICAL DATA

- Hammer face diameter: 60 mm
- Overall length: 400 mm
- Hammer head height: 150 mm
- Product dimensions: 400 x 150 x 69 mm (L x W x D)
- Weight: 1.64 kg
- EAN: 4010995266141

APPLICATIONS

Paving and tiling trade, drywall construction, assembly and dismantling work, building trade and workshop. Suited for measured positioning blows on components held in machine vices.

GS tested. Made in Poland (HS 82052000).