

Dead-blow soft-faced hammer 50 mm, hickory handle, round face - Wiha 02097

Item no. WH-02097

Manufacturer Wiha

EAN 4010995020972

The Wiha soft-faced hammer 800 with a 50 mm face diameter delivers measured positioning blows with zero recoil thanks to the metal-filled head, protecting joints, tendons and muscles. The medium-hard yellow face handles tool making, mechanical engineering, car repairs and sheet metal work. Both the hickory handle and the face are available as individual spare parts.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Poland
HS-Code	82052000
Weight	1.085 kg



DESCRIPTION

When precise positioning blows on sensitive surfaces are required, the dead-blow hammer 800 with its 50 mm face delivers controlled force without kickback. The metal filling eliminates recoil entirely, while the approximately 25 % greater head mass increases impact effect and reduces the physical effort required.

BENEFITS

- Dead-blow action protects joints, tendons and muscles via metal filling in the head
- Medium-hard yellow face (diameter 50 mm) for tool making, mechanical engineering, automotive and sheet metal work
- Approx. 25 % greater head mass for optimum impact with less physical effort
- High-grade hickory-wood handle with non-slip surface, ergonomically shaped
- Hickory handle and hammer face available individually as spare parts

TECHNICAL DATA

- Hammer face diameter: 50 mm
- Overall length: 385 mm
- Hammer head height: 135 mm
- Product dimensions: 385 x 135 x 50 mm (L x W x D)
- Weight: 1085 g

APPLICATIONS

Ideal for measured positioning blows on workpieces in machine vices, assembly work, tool and machine engineering, car repairs, and sheet metal and assembly operations. Made in Poland. HS code: 82052000. GS tested.