

Soft-Faced Hammer Safety Medium-Soft/Medium-Hard Hickory Handle Round 60 mm, 400 mm - Wiha 26437

Item no. WH-26437

Manufacturer Wiha

EAN 4010995264376

Wiha Safety soft-faced hammer with one medium-soft (black) and one medium-hard (yellow) round face and hickory handle, 60 mm face diameter, 400 mm overall length. GS tested - for demanding work in metalworking, paving and tile laying.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Poland
HS-Code	82052000
Weight	1.632 kg



DESCRIPTION

The Wiha Safety soft-faced hammer 60 mm in the medium-soft/medium-hard combination is the largest model in the Safety range with two different face hardnesses. Depending on the task, the user can choose between the black medium-soft caoutchouc face for tile and paving work and the yellow medium-hard polyurethane face for tool making and mechanical engineering. The recoiling impact effect eases stress on joints and reduces effort during repeated blows. The hickory handle with its non-slip surface is available separately as a spare part.

BENEFITS

- Medium-soft (black) / medium-hard (yellow) combination - two striking characters in one hammer
- Recoiling impact effect - noticeably less effort, especially during repeated blows
- 60 mm hammer face - wide contact zone for large workpieces
- Hickory handle 400 mm - high-grade, non-slip surface
- GS tested - verified safety to German testing standards
- Hammer faces and handle available as spare parts

TECHNICAL DATA

- Diameter, hammer face: 60 mm
- Overall length: 400 mm
- Hammer head height: 150 mm
- Dimensions: 400 x 150 x 69 mm (L x W x D)

- Material hardness: medium soft (black) / medium hard (yellow)
- Handle: hickory wood

APPLICATIONS

Tool and machine construction, sheet metal and assembly work, paving, tile laying and dry wall construction. Made in Poland, GS tested (HS 82052000).