

Torque Screwdriver TorqueFix permanently pre-set 0.4 Nm - Wiha 26925

Item no. WH-26925

Manufacturer Wiha

EAN 4010995269258

The Wiha TorqueFix torque screwdriver with a permanently pre-set torque of 0.4 Nm ensures controlled fastening of circular plug connectors with a hexagonal head. Release accuracy is $\pm 6\%$, traceable to national standards, with works inspection protocol and plastic box included.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	82054000
Weight	0.069 kg



STANDARDS & COMPLIANCE

ISO 6789

DESCRIPTION

For connections that must be tightened to exactly 0.4 Nm, the TorqueFix from Wiha provides a tamper-proof approach: the torque is permanently pre-set and cannot be accidentally altered. An audible and tactile click signal indicates when the set value is reached and prevents both under- and over-tightening.

BENEFITS

- Permanently pre-set torque 0.4 Nm - no risk of accidental adjustment
- Release accuracy $\pm 6\%$, traceable to national standards
- Audible and tactile click signal on torque release
- Ergonomic multi-component handle, lightweight and compact
- Compatible with all blades in the 2859 series (4 mm hexagon)
- Supplied in plastic box with works inspection protocol

TECHNICAL DATA

- Torque value (fixed): 0.4 Nm
- Tolerance: $\pm 6\%$
- Hexagon head: 4.0 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

- Handle diameter: 23 mm
- Handle length: 112 mm
- Product dimensions: 125 x 30 x 30 mm (L x W x D)
- Standard: DIN EN ISO 6789
- Origin: Germany (DEU)

APPLICATIONS

For controlled fastening of circular plug connectors with a hexagonal head at 0.4 Nm. Use in combination with a Wiha Torque 4 mm interchangeable blade. Custom pre-set torque values between 0.15 and 8 Nm available on request.