

Torque Screwdriver TorqueVario-S ESD 0.4-1.0 Nm Variably Adjustable - Wiha 26629

Item no. WH-26629

Manufacturer Wiha

EAN 4010995266295

The TorqueVario-S ESD torque screwdriver covers a variably adjustable torque range of 0.4 to 1.0 Nm for controlled fastening on ESD-sensitive components. The dissipative multi-component handle with a surface resistance of 10^6 to 10^9 ohms complies with IEC 61340-5-1. A clearly audible click confirms when the preset torque value is reached.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	82054000
Weight	0.139 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1 ISO 6789

DESCRIPTION

The TorqueVario-S ESD allows controlled tightening on components susceptible to electrostatic discharge, with a torque range of 0.4 to 1.0 Nm set continuously using the included Torque-Setter tool and integrated numeric scale. This covers a wide range of assembly tasks while protecting sensitive electronics from damage caused by over-torquing or electrostatic discharge.

BENEFITS

- ESD-safe dissipative handle with surface resistance 10^6 to 10^9 ohms, compliant with IEC 61340-5-1
- Infinitely adjustable torque range 0.4 to 1.0 Nm using the supplied Torque-Setter
- Audible and tactile click signal when the preset torque value is reached
- Release accuracy $\pm 6\%$, traceable to national standards per EN ISO 6789
- Ergonomic multi-component handle with 23 mm diameter, proportioned for the torque range
- Compatible with all interchangeable blades of the 2859 series (4 mm hexagon drive)

TECHNICAL DATA

- Torque range: 0.4 to 1.0 Nm
- Tolerance: $\pm 6\%$
- Hexagon drive: 4.0 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

- Handle diameter: 23 mm
- Handle length: 127 mm
- Product dimensions: 195 x 35 x 35 mm (L x W x D)
- Weight: 0.139 kg
- Scope of supply: screwdriver handle, Torque-Setter setting tool, works inspection protocol

APPLICATIONS

Designed for controlled screw tightening at a specified torque on electronic and ESD-sensitive assemblies in electronics manufacturing, device assembly, and maintenance work on sensitive hardware. Bit holder or blades are not included.

Made in Germany. Standards: DIN EN ISO 6789, IEC 61340-5-1. HS: 82054000.