

ESD grounding box with 3 x DK10 and Schuko earthing plug, 1 MΩ each - A1-ESD EP0102010

Item no. EP0102010

Manufacturer A1-ESD

Grounding box with three 10 mm snap connections at a 90-degree angle, each with a 1 MΩ protective resistor. The 3 m cable with a Schuko earthing plug connects the EPA workstation quickly to protective earth.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
ESD equipment	ESD-Erdnungskomponenten
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.05 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The A1-ESD grounding box EP0102010 bundles three earthing connections at one central point on the ESD workstation. The Schuko earthing plug uses the protective conductor of the existing socket as a safe ground point and links mats, earthing cables and personnel grounding to protective earth in a compliant way.

BENEFITS

- Three 10 mm snap connections for mats, earthing cables and personnel grounding
- 1 MΩ protective resistor per connection limits the discharge current to IEC 61340-5-1
- Mounted at a 90-degree angle for space-saving fitting at the bench edge
- 3 m cable with a Schuko earthing plug for direct connection to the socket

TECHNICAL DATA

- Connection: 3 x DK 10 mm snap
- Resistance: 1 MΩ protective resistor each
- Cable length: 3.00 m
- Grounding: Schuko earthing plug

- Mounting: 90-degree angle
- Selling unit: 1 piece

APPLICATION

Central grounding of ESD workstations where table mats, earthing cables and wrist straps are routed together to protective earth.

STANDARDS AND COMPLIANCE

Supports the IEC 61340-5-1 requirements for grounding within the EPA.