

Bernstein 9-341. ESD contact bracelet with spiral cord length 2.4m, yellow

Item no. BS-9-341

Manufacturer Bernstein

EAN 4250838527798

ESD contact bracelet with spiral cord length 2.4m, yellow

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Yellow
HS-Code	63079098
Weight	0.0099 kg



STANDARDS & COMPLIANCE

ESD safe DIN EN 61340-5-1 IEC 61340-5-1

DESCRIPTION

- EPA suitable. For working in electrostatically protected areas (ESD workplace / ESD protection zone).
- Meets the safety requirements for wrist grounding according to BGI 818 (DIN EN 61340-5-1)
- adjustable, anti-allergic, washable (incorporated silver and carbon threads)
- Bracelet length 220 mm
- press buttons 3-4 mm for wrist strap and 10 mm for ground contact connection
- highly elastic 2400 mm long spiral cable
- cable: 2 x 1 megohm safety resistor
- Bracelet: resistance 10^5 to 10^7
- color yellow
- weight 33 g

AREA OF APPLICATION

Wrist grounding, as a safe method to derive electrostatic charge from people, consists of an adjustable wrist strap with woven silver-plated synthetic fibers (close skin contact necessary) and a spiral cable which connects the wristband with the earthing point via press buttons, electrically dissipative. The coiled cable has a safety resistance of 1 MOhm on each connection side and is

approved for workplaces with a rated voltage up to 250 VAC. To ensure adequate insulation, the bracelet may only be stored in a dry place.

TECHNICAL DESCRIPTION

Washing instructions for the bracelet: machine wash up to 30 ° C with soft washing powder, drying at low temperature (warm not hot), do not bleach! Avoid contact with acidic / alkaline solvents. ESD protection is retained for about 30 washing process.

GENERAL INFORMATION

Please check your ESD workplace equipment regularly to ensure ESD compliant work (IEC 61340-5-1).