


Bernstein 14-681-VDE. VDE screwdriver cross-recess PH0 diam. 3.0 mm

Item no. **BS-14-681-VDE**Manufacturer **Bernstein**EAN **4250838509640**

VDE screwdriver cross-recess PH0 diam. 3.0 mm

TECHNICAL DATA

HS-Code	82054000
Weight	0.0099 kg



STANDARDS & COMPLIANCE

DIN IEC 60900 **EN 60900**

DESCRIPTION

- 2-component plastic handle
- shockproof handle
- safety insulated
- with functional hanging up hole
- blade hardened the whole length, burnished
- DIN 7438
- length 160 mm
- weight 27 g

AREA OF APPLICATION

BERNSTEIN quality VDE screwdriver 100% Made in Germany. The protective-coated blade is made of a high quality chrome vanadium steel and hardened over its entire length, the tip is burnished. The ergonomically shaped VDE multi-component handle is slip-proof, impact-resistant and has a practical hanging hole.

TECHNICAL DESCRIPTION

The quality is particularly evident in the manufacturing process of the blade. This is clamped in the quality test in a torque test rig and twisted to smooth breakage, this has to be done according to DIN in a very specific Newton meters range. Only a smooth break is safe! Inferior products can splinter or crack, which can be extremely dangerous.

GENERAL INFORMATION

Our VDE screwdrivers are under the control of the VDE test center. Each screwdriver of this series is individually tested according to the VDE guidelines DIN IEC 60900 / EN 60900 and approved for working under voltage up to 1000 volts. All insulations are REACH compliant and phthalate free.