

Fine Screwdriver PicoFinish ESD Slotted 2.0 x 40 mm - Wiha 43670

Item no. WH-43670

Manufacturer Wiha

EAN 4010995436704

The Wiha Fine Screwdriver PicoFinish ESD 43670 with 2.0 mm slotted tip protects ESD-sensitive components with a controlled surface resistance of $10^6 - 10^9$ ohm. The slim handle with quick-turning zone allows precise work on small slotted screws. Manufactured to IEC 61340-5-1, made in Germany.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Country of Manufacture **Germany**HS-Code **82054000**Weight **0.015 kg**

STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

For fastening tasks on ESD-sensitive electronic components, the PicoFinish ESD 43670 provides the right 2.0 mm slotted profile. The dissipative material reliably channels static energy away, while the slim handle gives a clear view of the fastening point and the tactile feedback needed for accurate torque control.

BENEFITS

- Electrostatically dissipative to IEC 61340-5-1, surface resistance $10^6 - 10^9$ ohm
- Slim handle with quick-turning zone for precise, rapid turning
- Smooth-running rotating cap for sensitive, controlled tightening
- Ergonomic handle design with soft zone for comfortable use
- Printed screwdriver symbols simplify profile selection

TECHNICAL DATA

- Slotted: 2.0 mm
- Visible blade length: 40 mm
- Round blade diameter: 2 mm
- Cutting strength: 0.4 mm

- Handle diameter: 18 mm
- Overall length: 140 mm
- Product dimensions: 142 x 17 x 17 mm (L x W x D)
- ESD article: Yes

APPLICATIONS

Ideal for fine and delicate fastening tasks on ESD-sensitive electronic components in electronics manufacturing, laboratory, and precision engineering environments.

Made in Germany. HS code 82054000. Manufactured to IEC 61340-5-1.