

## Insulated Square Adapter 3/8" to 1/4" for Nut Drivers up to 25 Nm, VDE - Wiha 44355

Item no. WH-44355

Manufacturer Wiha

EAN 4010995443573

The Wiha square adapter 44355 connects the insulated 3/8" torque key to insulated 1/4" nut driver inserts, transmitting up to 25 Nm for controlled fastening and loosening of hex screws. Individual piece tested to DIN EN/IEC 60900 for safe work on live parts up to 1,000 V AC. Compatible only with the insulated 3/8" Wiha torque key up to 25 Nm.

### TECHNICAL DATA

|                        |          |
|------------------------|----------|
| Ausführungsklasse      | TEC      |
| Country of Manufacture | Germany  |
| HS-Code                | 84661038 |
| Weight                 | 0.115 kg |



## STANDARDS & COMPLIANCE

IEC 60900

## DESCRIPTION

The Wiha square adapter 44355 bridges the 3/8" torque key drive with the wider selection of 1/4" nut driver inserts. Designed specifically for work on live parts and individually tested to IEC 60900, it maintains full electrical protection throughout the torque transmission chain.

## BENEFITS

- Bridges 3/8" drive with 1/4" nut driver inserts, expanding the range of usable socket sizes
- Power transmission up to 25 Nm for controlled fastening and loosening of hex screws and nuts
- Fully insulated, individual piece tested to DIN EN/IEC 60900 for safe use on live parts up to 1,000 V AC
- VDE-certified

## TECHNICAL DATA

- Drive: 3/8" square
- Socket: 1/4" square
- Max. torque: 25 Nm
- Overall length: 100 mm
- Dimensions: 99 x 22 x 22 mm (L x W x D)

- Standard: DIN EN/IEC 60900

## **APPLICATIONS**

- Use in combination with the insulated Wiha 3/8" torque key (max. 25 Nm)
- Fastening hex screws on live parts up to 1,000 V AC
- For use only with insulated Wiha nut driver inserts

Made in Germany. Standard: DIN EN/IEC 60900. HS code: 84661038.