

Bit Set XLSelector Security Standard 25 mm, 31-pcs. 1/4" C6,3, Assorted - Wiha 29416

Item no. WH-29416

Manufacturer Wiha

EAN 4010995294168

The Wiha XLSelector Security bit set contains 31 standard 25 mm security bits - Tri-Wing®, Spanner, Hexagon with hole, Torq-Set®, TORX® Tamper Resistant and internal square - plus a CentroFix quick-change holder. The patented torsion zone protects against premature breakage; the compact plastic box (135 x 78 x 18 mm) makes bit removal effortless. Standard: DIN 3126, ISO 1173, Style C6.3.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Vietnam
HS-Code	82079030
Weight	0.267 kg



STANDARDS & COMPLIANCE

ISO 1173 DIN 3126

DESCRIPTION

The XLSelector Security bit set covers all common security screw types in one compact set. The CentroFix quick-change holder is magnetic and enables rapid bit changes without switching tools; the torsion zone absorbs impact loads and protects the bit from premature breakage.

BENEFITS

- 31 security bits in one set - Tri-Wing®, Spanner, Hexagon with hole, Torq-Set®, TORX® TR and internal square
- Patented torsion zone (ZOT) - protects against premature breakage under load
- CentroFix quick-change holder, magnetic, E 6.3 - secure retention and fast bit changes
- Compact plastic box 135 x 78 x 18 mm with easy bit removal
- Soft zones on housing for comfortable handling

TECHNICAL DATA

- Shank: 1/4" C6.3
- Length: 25 mm standard
- Standard: DIN 3126, ISO 1173, Style C6.3
- Bits: Tri-Wing® 0/1/2/3/4, Spanner 4/6/8/10 mm, Hexagon with hole 2/2.5/3/4/5/6 mm, Torq-Set®

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

6/8/10, TORX® TR T8H/T9H/T10H/T15H/T20H/T25H/T27H/T30H/T40H, Internal square #1/#2/#3

- Accessories: CentroFix quick-change holder magnetic E 6.3, XLSelector
- Made in Vietnam

APPLICATIONS

For fastening with security screws in electronics, household appliances, automotive and industrial equipment - wherever tamper-resistant fixings need to be accessed or inspected.