

C.K T4880XES257. Xonic ESD screwdriver slot, 2.5x75 mm, 172 mm

Item no. WL11142

Manufacturer C.K

Xonic ESD screwdriver slot, 2.5x75 mm, 172 mm

Kein Produktbild

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Weight **0.1 kg**

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

OTHER VERSIONS

item number	blade width	blade thickness	tool length
WL11137	0.8 mm	0.2 mm	157 mm
WL11138	1.2 mm	0.25 mm	157 mm
WL11139	1.5 mm	0.3 mm	157 mm
WL11140	1.8 mm	0.3 mm	157 mm
WL11141	2.5 mm	0.4 mm	157 mm
WL11142	2.5 mm	0.4 mm	172 mm
WL11143	3 mm	0.5 mm	197 mm
WL11144	3 mm	0.5 mm	250 mm
WL11146	4 mm	0.6 mm	197 mm

- Ergonomically designed handle with rotating trough cap for optimum control of the rotary movement even at lowest torques
- High quality chrome-vanadium steel shaft for exceptional strength and durability
- Precisely fitting tips for exact adjustments and damage-free screwing in
- Black blades, not chrome-plated, avoid reflections and flaking of chrome particles
- Fully ESD compliant, dissipative in all areas

- Size: 2,5 mm
- Visible blade length: 75 mm
- total length: 172 mm

PRODUCT DETAILS

item number	WL11142
model	4880X-ESD-2,5x75
manufacturer	C.K
manufacturer item number	T4880XES257
dimensions (LxWxH)	0 x 17 mm x 17 mm
dimensions with packaging (LxWxH)	220 mm x 17 mm x 17 mm
order unit	piece
ESD safe	yes
VDE	no
type of screwdriver	normal screwdrivers
type of screw	slot
packaging mass	piece
tool length	172 mm
usage screwdriver	slotted screws
blade width	2.5 mm
blade thickness	0.4 mm