

Dispensing needle olive GA 14, ID 1.54 mm, straight, 1/2" - Nordson EFD 7018043

Item no. WL11680

Manufacturer Nordson EFD

Straight Optimum all-purpose dispensing needle in gauge 14 with a 1.54 mm inner diameter for precise application of assembly materials. The polished, passivated stainless steel capillary dispenses burr-free and drip-free. The polypropylene hub with luer-lock thread seats firmly on the barrel.

TECHNICAL DATA

Weight

0.1 kg



DESCRIPTION

The straight Optimum all-purpose dispensing needle in gauge 14 delivers precise, repeatable material application through its 1.54 mm inner diameter.

- Capillary in burr-free, polished and passivated stainless steel
- Precise, consistent application with no leaks, drip-free
- Capillary length 1/2" (12.7 mm) for work close to the part
- Inner diameter 1.54 mm, gauge 14, olive colour code
- Polypropylene hub with luer-lock thread for a secure fit

TECHNICAL DATA

Model	5114-B / 7018043
Manufacturer	Nordson EFD
Manufacturer item no.	7018043
Gauge	GA 14
Inner diameter	1.54 mm
Outer diameter	1.83 mm
Capillary length	1/2" (12.7 mm)
Tip shape	straight

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Colour	olive
Capillary material	stainless steel
Hub	polypropylene, luer-lock
ESD safe	no
Order unit	piece

Suited to low to medium-viscosity adhesives and assembly materials. Fits Optimum barrels and luer-lock manual dispensers via the luer-lock thread.