

Dispensing needle conical SmoothFlow 16 GA grey, 1.19 mm ID - Nordson EFD 7018100

Item no. **WL11691**

Manufacturer **Nordson EFD**

Conical Optimum SmoothFlow dispensing needle in plastic for medium to high viscosity fluids. The smooth tapered bore lowers back pressure and lays down thick or filled media evenly. Gauge 16 GA (grey) with Luer-Lock thread.

TECHNICAL DATA

Colour	Grey
Weight	0.1 kg



DESCRIPTION

The conical Optimum SmoothFlow dispensing needle guides the medium through a steadily tapering bore. This lowers the dispensing pressure and keeps the flow calm even with thick fluids.

- Smooth tapered bore cuts back pressure and dripping
- Gauge 16 GA in grey for size identification
- Inner diameter 1.19 mm at the outlet for a defined bead
- Polyethylene with UV blocker for light-sensitive media
- Luer-Lock thread seats leak-free on the barrel

TECHNICAL DATA

Model	5116TT-B / 7018100
Manufacturer	Nordson EFD
Manufacturer part no.	7018100
Gauge	16 GA
Inner diameter	1.19 mm
Capillary length	1.24"
Colour	grey
Tip shape	conical

Material	polyethylene with UV blocker
Connection	Luer-Lock
Order unit	piece
ESD safe	no

Suited to medium to high viscosity and filled fluids such as pastes, greases and filled adhesives. Fits Nordson EFD Optimum syringe barrels with Luer-Lock thread.