

Dispensing needle GA 20, 1/2", pink, ID 0.61 mm - Nordson EFD 7018178

Item no. WL11699

Manufacturer Nordson EFD

This Optimum® general-purpose dispensing needle in passivated stainless steel applies adhesives and assembly materials cleanly and drip-free. Inner diameter 0.61 mm (gauge 20, colour code pink), capillary length 1/2" for good control at the workpiece. The Luer-lock hub fits Optimum® syringe barrels.

TECHNICAL DATA

Colour	Pink
Weight	0.1 kg



DESCRIPTION

The Optimum® general-purpose dispensing needle in burr-free, polished and passivated stainless steel applies assembly materials cleanly and drip-free, at a 0.61 mm inner diameter (GA 20).

- Precise, consistent material output without stringing
- Burr-free polished stainless steel for a drip-free output
- Capillary length 1/2" for targeted access at the workpiece
- Polypropylene Luer-lock hub for Optimum® syringe barrels
- Colour code pink marks gauge 20 for fast selection

TECHNICAL DATA

Model	5120-B / 7018178
Manufacturer	Nordson EFD
Manufacturer part no.	7018178
Gauge	GA 20
Inner diameter	0.61 mm
Outer diameter	0.91 mm
Capillary length	1/2"
Colour	pink

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Tip shape	straight
Material	Passivated stainless steel, polypropylene hub
Sales unit	piece
ESD-safe	no

Suited to low to medium viscosity adhesives, greases, oils and solder pastes. Fits Optimum® syringe barrels and dispensing syringes with a Luer-lock connection.