

Bent 45° dispensing needle GA 20, 1/2", pink, ID 0.61 mm - Nordson EFD 7018179

Item no. WL11703

Manufacturer Nordson EFD

This bent Optimum® stainless steel needle with SafetyLok hub dispenses at a 45° angle and reaches poorly visible spots precisely. Inner diameter 0.61 mm (gauge 20, colour code pink), capillary length 1/2". The passivated stainless steel gives a clean, drip-free application.

TECHNICAL DATA

Colour	Pink
Weight	0.1 kg



DESCRIPTION

The bent Optimum® stainless steel needle with SafetyLok hub dispenses at a 45° angle, reaching hidden spots precisely and repeatably, at a 0.61 mm inner diameter (GA 20).

- 45° bend for dispensing under components and along edges
- Passivated stainless steel for a drip-free, clean output
- SafetyLok hub locks the needle against blow-off under pressure
- Capillary length 1/2" for targeted access
- Colour code pink marks gauge 20

TECHNICAL DATA

Model	5120-45-B / 7018179
Manufacturer	Nordson EFD
Manufacturer part no.	7018179
Gauge	GA 20
Inner diameter	0.61 mm
Outer diameter	0.91 mm
Capillary length	1/2"
Colour	pink

Tip shape	bent, 45°
Material	Passivated stainless steel, polypropylene hub (SafetyLok)
Sales unit	piece
ESD-safe	no

Suited to low to medium viscosity adhesives, greases, oils and solder pastes. Fits Optimum® syringe barrels with a Luer-lock connection.