

Dispensing needle blue GA 22 straight, 1.5" (38 mm), ID 0.41 mm - Nordson EFD 7018266

Item no. WL11714

Manufacturer Nordson EFD

The Optimum general-purpose dispensing needle applies adhesives, greases and other assembly fluids through a burr-free stainless steel capillary in gauge 22 (0.41 mm inner diameter) with precise, drip-free flow. Gauge 22 colour-coded blue, capillary length 1.5" (38 mm).

TECHNICAL DATA

Colour	Blue
Weight	0.1 kg



DESCRIPTION

The Optimum general-purpose dispensing needle applies adhesives, greases and other assembly fluids through a burr-free stainless steel capillary in gauge 22 (0.41 mm inner diameter) with precise, drip-free flow.

- Colour-coded blue hub marks gauge 22 and speeds needle changes at the bench.
- Polished, passivated stainless steel keeps flow even and residue-free.
- Capillary length 1.5" (38 mm) reaches recessed joints.
- Luer-Lock thread locks onto Optimum barrels and syringes.

TECHNICAL DATA

Model	5122-1,5-B / 7018266
Manufacturer part no.	7018266
Manufacturer	Nordson EFD
Gauge	GA 22 (0.39-0.43 mm)
Inner diameter	0.41 mm
Outer diameter	0.72 mm
Capillary length	1.5" (38 mm)
Tip shape	straight

Colour	blue
Material	passivated stainless steel
Receptacle	Polypropylene with Luer-Lock thread
Order unit	piece
ESD safe	no

Suited to low and medium viscosity materials such as adhesives, greases and oils. Fits Optimum dispensing barrels and Luer-Lock syringes.