

Dispensing needle red 0.5" straight GA 25 ID 0.25 mm - Nordson EFD 7018345

Item no. WL11720

Manufacturer Nordson EFD

Optimum general-purpose dispensing needle in polished, passivated stainless steel for precise, drip-free application. The straight GA 25 cannula with a 0.25 mm inner diameter in the red colour code lays down even beads without stringing. The Luer-Lock thread seats securely on Optimum syringe barrels and manual dispensers.

TECHNICAL DATA

Colour	Red
Weight	0.1 kg



DESCRIPTION

For the precise application of low to medium viscosity adhesives and sealants, this Optimum dispensing needle with GA 25 and a 0.25 mm inner diameter delivers an even, drip-free flow.

- Burr-free, polished stainless steel cannula for a clean cut-off without stringing (0.25 mm inner diameter)
- red colour code to GA 25 for fast needle selection at the workstation
- Cannula length 0.5" (12.7 mm) for targeted access to the joint
- Luer-Lock thread for a firm, leak-free fit on Optimum syringe barrels

TECHNICAL DATA

Property	Value
Model	5125-B
Manufacturer part no.	7018345
Manufacturer	Nordson EFD
Gauge	GA 25
Inner diameter	0.25 mm
Outer diameter	0.52 mm
Cannula length	0.5" (12.7 mm)

Property	Value
Tip shape	straight
Colour code	red
Material	stainless steel, polished and passivated, polypropylene hub
Connection	Luer-Lock thread
Order unit	piece
ESD safe	no

Fits Optimum syringe barrels, bayonet adapters and manual dispensers via the Luer-Lock thread.
 Suited to low and medium viscosity adhesives, oils, fluxes and silicones.