

Knipex 26 22 200. Needle nose pliers with cutting edge (cranesbill pliers), black atramentized, 200 mm

Item no. WL13351

Manufacturer Knipex

Needle nose pliers with cutting edge (cranesbill pliers), black atramentized, 200 mm

TECHNICAL DATA

Colour **Black**

Weight **0.1 kg**



STANDARDS & COMPLIANCE

ISO 5745

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point
WL13351	nein
WL61415	ja

Flat round nose pliers with cutting edge Elastic tips: dimensionally stable even when twisted. Torsion-tolerant, elastic precision tips. Flat-round, long, pointed jaws. With cutting edges for soft, medium-hard and hard wire. Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC. 40° angled jaws. - Cutting value medium hard wire (diameter): Ø 3,2mm - Cutting value hard wire (diameter): Ø 2,2mm - Jaw thickness (at joint) (T1): 9,5mm - Tip width (E): 3,0mm - Tip thickness (D1): 2,5mm - Gripping surface length (L4): 23,0mm - Jaw length (L3): 73,0mm - Head angle: 40 - Head width (W3): 18mm - Shape: 2

- Torsion-tolerant, elastic precision tips
- Flat-round, long, tapered jaws
- With cutting edges for soft, medium-hard and hard wire

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

- Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC

PRODUCT DETAILS

item number	WL13351
model	26 22 200
manufacturer	KNIPEX
manufacturer item number	26 22 200
dimensions (LxWxH)	205 mm x 53 mm x 19 mm
dimensions with packaging (LxWxH)	229 mm x 119 mm x 52 mm
Packaging volume	1.417 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 5745
RoHS conform	no
surface	black atramentised
tether attachment point	nein
ESD safe	no
VDE	no
tool length	200 mm
type of handle	With multi-component handles
cutting value wire diameter hard	2.2 mm
cutting value wire diameter medium	3.2 mm
type of pliers	snipe nose pliers