

Knipex 26 27 200. Needle nose pliers with cutting edge (cranesbill pliers), chrome-plated, insulated 200 mm

Item no. WL13352

Manufacturer Knipex

Needle nose pliers with cutting edge (cranesbill pliers), chrome-plated, insulated 200 mm

TECHNICAL DATA

Certification	IEC 60900
Norm	DIN ISO 5745
Weight	0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5745 IEC 60900

DESCRIPTION

Flat round nose pliers with cutting edge Elastic tips: dimensionally stable even when twisted. Torsion-tolerant, elastic precision tips. Flat-round, long, pointed jaws. With cutting edges for soft, medium-hard and hard wire. Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC. 40° angled jaws. - Cutting value medium-hard wire (diameter): Ø 3.2mm - Cutting value hard wire (diameter): Ø 2.2mm - Jaw thickness (at joint) (T1): 9.5mm - Tip width (E): 3.0mm - Tip thickness (D1): 2.5mm - Gripping surface length (L4): 23.0mm - Jaw length (L3): 73.0mm - Head angle: 40 - Head width (W3): 18mm - Shape: 2 - VDE-tested: Yes

- Torsion-tolerant, elastic precision tips
- Flat-round, long, tapered jaws
- With cutting edges for soft, medium-hard and hard wire
- Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC

PRODUCT DETAILS

item number	WL13352
model	26 27 200

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

manufacturer	KNIPEX
manufacturer item number	26 27 200
dimensions (LxWxH)	205 mm x 59 mm x 28 mm
dimensions with packaging (LxWxH)	211 mm x 66 mm x 30 mm
Packaging volume	0.535 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5745 IEC 60900
RoHS conform	no
surface	chrome-plated
ESD safe	no
VDE	no
type of handle	Dip-insulated, VDE-tested
cutting value wire diameter hard	2.2 mm
cutting value wire diameter medium	3.2 mm
type of pliers	snipe nose pliers