

Knipex 78 61 125. Electronic-Super-Knips, side cutter for fiberGlasss, 125 mm

Item no. WL13362

Manufacturer Knipex

Electronic-Super-Knips, side cutter for fiberglass, 125 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 9654

DESCRIPTION

Electronic Super Knips® precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Ground, very sharp cutting edges without facet. Exactly shaped tips also cut adjacent wires from Ø 0.2 mm. Shear cut with controlled micro cutting edge offset for long life and ultra-precise cutting of even the thinnest wires. Joint with stainless steel rivet. Extremely smooth action for fatigue-free work. With opening spring and opening limiter. Also suitable for cutting fibre optic cables (optical fibres). Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Special tool steel, multi-stage oil-hardened. - Shape: 6 - Cutting values medium hard wire (diameter): Ø 1,2mm - Cutting values soft wire (diameter): Ø 0,2 - 1,6mm - Jaw length (B): 9mm - Jaw thickness (at joint) (D): 7,5mm - Head width (A): 13,5mm

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Ground, very sharp cutting edges without facet
- Exactly shaped tips also cut adjacent wires from Ø 0.2 mm
- Shear cut with controlled micro cutting edge offset for long service life and ultra-precise cutting of even the thinnest wires
- Joint with stainless steel rivet

- Extremely smooth action for fatigue-free work
- With opening spring and opening limiter

PRODUCT DETAILS

item number	WL13362
model	78 61 125
manufacturer	KNIPEX
manufacturer item number	78 61 125
dimensions (LxWxH)	130 mm x 62 mm x 13 mm
dimensions with packaging (LxWxH)	189 mm x 72 mm x 48 mm
Packaging volume	0.64 dm ³
order unit	piece
type of packaging	single pack
standards	DIN ISO 9654
product series	Electronic-Super-Knips®
RoHS conform	no
surface	burnished
Cut form	without bevel
ESD safe	no
VDE	no
tool length	125 mm
type of side cutter	side cutter
type of handle	With multi-component sheaths
cutting value wire diameter medium	1.2 mm
cutting value wire diameter soft	1.6 mm