

Knipex 95 06 230. Cable shears, insulated, handles molded with plastic, VDE-tested, 230 mm

Item no. WL13366

Manufacturer Knipex

Cable shears, insulated, handles molded with plastic, VDE-tested, 230 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

EN 60900 IEC 60900

DESCRIPTION

Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. No crushing, low deformation of the cable. Adjustable screw joint. For solid copper conductors up to 16 mm², stranded up to 50 mm² and fine stranded up to 70 mm²; for stranded aluminium conductors 70 mm². Easy cutting with one-hand operation due to high transmission ratio. Stainless special steel, hardened and tempered. - Cutting value Cu-cable, stranded: 50mm² - Cutting value Cu-cable, stranded: Ø 16mm - AWG: 1 / 0 - VDE-tested: Yes

- Not suitable for steel wire and hard-drawn copper conductors
- Hardened cutting edges with precision grinding
- No crushing, low deformation of the cable

PRODUCT DETAILS

item number	WL13366
model	95 06 230
manufacturer	KNIPEX

manufacturer item number	95 06 230
dimensions (LxWxH)	225 mm x 82 mm x 30 mm
dimensions with packaging (LxWxH)	252 mm x 86 mm x 36 mm
Packaging volume	0.744 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900 IEC 60900
RoHS conform	no
VDE	no
ESD safe	no
tool length	230 mm
type of side cutter	cable cutter
AWG	1 / 0
type of handle	Insulated, overmoulded with plastic, VDE-tested
Cutting value copper cable, multistranded	50 mm ²
Cutting value copper cable, multistranded (diameter)	16 mm