

## ESD desoldering braid, white, width 0.9 mm, length 3 m - Techspray 1808-10F

Item no. **WL15046**

Manufacturer **Techspray**

ESD-safe desoldering braid, white, 0.9 mm wide, 3 m on a reel. Rosin-flux-impregnated copper braid wicks molten solder away quickly and cleanly when reworking circuit boards.

### TECHNICAL DATA

|                        |                         |
|------------------------|-------------------------|
| Ausführungsklasse      | <b>ESD (antistatic)</b> |
| Colour                 | <b>White</b>            |
| Country of Manufacture | <b>United States</b>    |
| HS-Code                | <b>85159080900</b>      |
| Weight                 | <b>0.1 kg</b>           |



### STANDARDS & COMPLIANCE

**ESD safe** IEC 61340-5-1

### DESCRIPTION

The Techspray 1808-10F is an ESD-safe desoldering braid 0.9 mm wide, supplied on a 3 m reel. The flux-impregnated copper braid wicks molten solder away by capillary action and keeps the joint clean.

### BENEFITS

- Rosin-flux impregnated for fast, clean solder wicking
- Fine copper braid for even capillary action
- 0.9 mm width suited to fine SMD pads
- ESD-safe reel for work on static-sensitive components

### TECHNICAL DATA

|                  |           |
|------------------|-----------|
| Item no.         | WL15046   |
| Model            | 1808-10F  |
| Manufacturer     | Techspray |
| Manufacturer no. | 1808-10F  |

|          |                   |
|----------|-------------------|
| Width    | 0.9 mm            |
| Length   | 3000 mm           |
| Content  | 3 m               |
| Colour   | white             |
| Flux     | Rosin / colophony |
| ESD-safe | yes               |

## APPLICATIONS

Desoldering and reworking printed circuit boards, removing solder bridges and excess solder.  
Suitable for removing solder and reworking printed circuit boards.

## COMPATIBILITY AND SCOPE OF DELIVERY

Supplied as a 3 m reel (manufacturer no. 1808-10F). ESD-safe to IEC 61340-5-1, RoHS compliant.