

ESD desoldering braid, green, width 1.9 mm, length 3 m - Techspray 1810-10F

Item no. WL15057

Manufacturer Techspray

ESD-safe desoldering braid, green, 1.9 mm wide, 3 m on a reel. Rosin-flux-impregnated copper braid wicks molten solder away quickly and cleanly when reworking circuit boards.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Green
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Techspray 1810-10F is an ESD-safe desoldering braid 1.9 mm wide, supplied on a 3 m reel. The flux-impregnated copper braid wicks molten solder away by capillary action and keeps the joint clean.

BENEFITS

- Rosin-flux impregnated for fast, clean solder wicking
- Fine copper braid for even capillary action
- 1.9 mm width suited to wider pads and through-hole leads
- ESD-safe reel for work on static-sensitive components

TECHNICAL DATA

Item no.	WL15057
Model	1810-10F
Manufacturer	Techspray
Manufacturer no.	1810-10F

Width	1.9 mm
Length	3000 mm
Content	3 m
Colour	green
Flux	Rosin / colophony
ESD-safe	yes

APPLICATIONS

Desoldering and reworking printed circuit boards, removing solder bridges and excess solder.
Suitable for removing solder and reworking printed circuit boards.

COMPATIBILITY AND SCOPE OF DELIVERY

Supplied as a 3 m reel (manufacturer no. 1810-10F). ESD-safe to IEC 61340-5-1, RoHS compliant.