

Bahco BE-8010. Ergo Screwdriver for slotted screws, straight, with 3-component handle, 0.4 mm x 2.5 mm x 60 mm

Item no. WL16075

Manufacturer Bahco

ERGO Screwdriver for slotted screws, straight, with 3-component handle, 0.4 mm x 2.5 mm x 60 mm

TECHNICAL DATA

Weight 0.1 kg



STANDARDS & COMPLIANCE

ISO 2380 DIN 5264

DESCRIPTION

OTHER VERSIONS

item number	blade width	blade thickness	blade length
WL16075	2.5 mm	0.4 mm	60 mm
WL16086	2.5 mm	0.4 mm	75 mm
WL16077	3 mm	0.5 mm	60 mm
WL16078	3 mm	0.5 mm	75 mm
WL16087	3 mm	0.5 mm	125 mm
WL16079	3.5 mm	0.6 mm	75 mm
WL16089	3.5 mm	0.6 mm	125 mm
WL16080	4 mm	0.8 mm	100 mm
WL16090	4 mm	0.8 mm	175 mm
WL20734	5.5 mm	1 mm	200 mm
WL19948	8 mm	1.6 mm	175 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/3

item number	blade width	blade thickness	blade length
WL53430	2 mm	0.3 mm	60 mm
WL53432	3 mm	0.5 mm	100 mm
WL53447	3 mm	0.5 mm	200 mm
WL53449	3.5 mm	0.6 mm	200 mm
WL53450	5.5 mm	1 mm	125 mm
WL53452	6 mm	1 mm	150 mm
WL53688	5.5 mm	1 mm	150 mm
WL53689	6.5 mm	1.2 mm	150 mm

- Screwdriver developed in the course of the ERGO™ process
- For slotted screws
- Burnished tip for greater accuracy
- 3-component handle for maximum ease of use, soft material with rigid surface provides comfortable grip and better power transmission
- Maximum comfort with minimum effort due to ergonomic design
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2 to 3.5
- Flat sides prevent rolling away
- integrated suspension opening
- High performance steel alloy blade, chrome plated and fully hardened for maximum corrosion protection and long life
- Standards: ISO 2380 and DIN 5264

PRODUCT DETAILS

item number	WL16075
model	BE 8010
manufacturer	BAHCO
manufacturer item number	BE-8010
dimensions (LxWxH)	270 mm x 60 mm x 45 mm
order unit	piece
type of screwdriver	normal screwdrivers
Blade thickness	0.4 mm
Handle width	17 mm
type of screw	slot
handle length	122 mm
ESD safe	no
VDE	no
packaging mass	piece

tool length	182 mm
handle diameter	17 mm
blade length	60 mm
blade width	2.5 mm
blade thickness	0.4 mm