

Bahco BE-8230S. Ergo Insulated screwdriver for slotted screws with 3-component handle, VDE-certified 0.6 mmx3.5 mmx100 mm

Item no. WL18286

Manufacturer Bahco

ERGO Insulated screwdriver for slotted screws with 3-component handle, VDE-certified 0.6 mmx3.5 mmx100 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

IEC 60900 ISO 2380 DIN 5264

DESCRIPTION

OTHER VERSIONS

item number	blade width & Blade thickness	blade length
WL16076	2.5 mm & 0.4 mm	2.5 mm
WL16088	3 mm & 0.5 mm	2.9 mm
WL18286	3.5 mm & 0.6 mm	3.43 mm
WL16081	4 mm & 0.8 mm	100 mm
WL16082	5.5 mm & 1 mm	125 mm
WL21092	8 mm & 1.2 mm	175 mm
WL53456	10 mm & 1.6 mm	200 mm
WL53458	12 mm & 2 mm	200 mm
WL53690	6.5 mm & 1.2 mm	150 mm

- Developed as part of the ERGO™ process
- Insulated ERGO™ Screwdrivers for slotted screws

- Burnished tip for higher accuracy
- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- Flat side parts prevent rolling away
- Integrated suspension eye
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2.5 to 3.5
- High performance steel alloy, the insulation layer is sprayed directly onto the blade
- For work on live workpieces, up to 1000 V
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 2380/DIN 5264

PRODUCT DETAILS

item number	WL18286
model	BE 8230S
manufacturer	BAHCO
manufacturer item number	BE-8230S
dimensions (LxWxH)	270 mm x 60 mm x 40 mm
order unit	piece
Blade thickness	0.6 mm
type of screwdriver	1000 V insulated
Handle width	17 mm
handle length	122 mm
VDE	yes
ESD safe	no
type of screw	slot
packaging mass	piece
tool length	222 mm
handle diameter	17 mm
blade length	3.43 mm
blade width	3.5 mm