

Bahco BE-8630S. Ergo Insulated screwdriver for Phillips screws with 3-component handle, VDE-certified PH3x36 mmx150 mm

Item no. WL18290

Manufacturer Bahco

ERGO Insulated screwdriver for Phillips screws with 3-component handle, VDE-certified PH3x36 mmx150 mm

TECHNICAL DATA

Weight

0.1 kg



STANDARDS & COMPLIANCE

ISO 8764 IEC 60900 DIN 5260

DESCRIPTION

OTHER VERSIONS

item number	type of screw	Handle width	blade length	tool length
WL18287	PH0	17 mm	75 mm	197 mm
WL18288	PH1	27 mm	80 mm	202 mm
WL18289	PH2	36 mm	100 mm	222 mm
WL18290	PH3	36 mm	150 mm	272 mm
WL18291	PH4	36 mm	200 mm	361 mm
WL53474	PH1	27 mm	150 mm	272 mm
WL53478	PH2	27 mm	100 mm	222 mm
WL53480	PH2	36 mm	175 mm	297 mm

- Developed as part of the ERGO™ process
- Insulated ERGO™ VDE Screwdrivers for cross-heads
- Burnished tip for higher accuracy

- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- Maximum comfort and minimum stress thanks to the ergonomic design
- Colour marking at the end of the handle for quick identification of the blade type
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, size PH0
- Flat side parts prevent rolling away
- Integrated suspension eye
- Flat side parts prevent rolling away
- Standards: ISO 8764/DIN 5260, IEC 60900, VDE certified
- Blade made of high-performance steel alloy
- For work on live workpieces, up to 1000 V
- High-quality insulation layer, which is sprayed directly onto the blade
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V
- The correct tip can easily be identified by the colour marking on the handle

PRODUCT DETAILS

item number	WL18290
model	BE 8630S
manufacturer	BAHCO
manufacturer item number	BE-8630S
dimensions (LxWxH)	310 mm x 105 mm x 37 mm
order unit	piece
ESD safe	no
handle length	122 mm
type of screwdriver	1000 V insulated
type of screw	PH3
VDE	yes
packaging mass	piece
Handle width	36 mm
tool length	272 mm
handle diameter	36 mm
blade length	150 mm