

Entlötdüse für Padreinigung mit 1 mm Innendurchmesser für DR560-A - JBC C560013


Item no. WL19925

Manufacturer JBC

C560 Series desoldering nozzle with 1 mm inside diameter for pad cleaning. The pronounced contact-surface slot channels the suction air across the pad to clear residual solder reliably.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Country of Manufacture	Spain
HS-Code	85159080900
Series	C560
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

After a component has been removed, the C560013 desoldering nozzle restores clean pads before re-population. The pronounced contact-surface slot guides the suction air straight across the pad and draws off molten solder quickly.

BENEFITS

- 1 mm inside diameter for slightly larger pads and plated through-holes
- Contact-surface slot circulates the suction air for thorough pad cleaning
- Instant heating and excellent heat transfer of the C560 series
- Matched directly to the DR560 desoldering iron

TECHNICAL DATA

Item number	WL19925
Model	C560-013
Manufacturer item number	C560013
Tip series	C560

Inside diameter	1 mm
Outside diameter	2.7 mm
Application	Pad cleaning
Suitable handpiece	DR560
Dimensions with packaging (LxWxH)	155 x 55 x 45 mm
Order unit	piece

APPLICATIONS

Cleaning solder pads and plated through-holes after desoldering THT components, preparing the board for repair and re-population.

COMPATIBILITY & SCOPE OF SUPPLY

Fits the JBC DR560 desoldering iron (DR560-A). Supplied as a single piece. ESD-safe to IEC 61340-5-1, RoHS compliant. Made in Spain.