

Filter trolley ACD Jumbo-VF for chemical vapours 80 m³/h - ULT ACD JUMBO 2.0-BM.3.0

Item no. WL20426

Manufacturer ULT

Workplaces that move need extraction that moves with them. The ACD Jumbo-VF rolls up to the process on castors with a telescopic handle and delivers 80 m³/h at 1900 Pa, up to 190 m³/h maximum. An adsorption cassette of roughly 6 kg binds the vapours while the flow control matches the output to the task.

TECHNICAL DATA

Weight	49.6 kg
--------	----------------



DESCRIPTION

Chemical vapours rarely arise at one fixed bench. This filter trolley works as a storage filter unit at 80 m³/h against 1900 Pa, reaches 3200 Pa of vacuum and is pulled to the job with its telescopic handle.

BENEFITS

- Adsorption filter cassette of approx. 6 kg (ULT 02.1.240) as a storage filter, replaced once saturated
- Nominal flow of 80 m³/h at 1900 Pa, up to 190 m³/h and 3200 Pa vacuum
- Volume flow control and optical particle filter loading indicator as standard
- Adjustable suction plate, suction nozzles available in 50, 63 and 75 mm
- Adjustable blow-out opening, the nozzle can be replaced by an exhaust hose
- Quiet operation at 45-49 dBA on a compact 340 x 450 mm footprint

TECHNICAL DATA

Item number	WL20426
Model	ACD Jumbo-VF filter trolley
Manufacturer	ULT
Manufacturer item number	ACD JUMBO 2.0-BM.3.0

Dimensions (LxWxH)	340 mm x 450 mm x 530 mm
Weight	49.6 kg
Order unit	piece
Motor rating	0.15 kW
Nominal volume flow	80 m³/h at 1900 Pa
Volume flow max.	190 m³/h
Vacuum max.	3200 Pa
Voltage	230 V
Frequency	50/60 Hz
Nominal current	0.95 A
Noise level	45-49 dBA
Filter	adsorption filter cassette approx. 6 kg (ULT 02.1.240)
Suction nozzles	50 mm, 63 mm, 75 mm
Equipment	special blower, volume flow control, filter loading indicator

APPLICATIONS

Capture of solvent and adhesive vapours, odours and chemical outgassing at dispensing, potting, cleaning and repair benches. Because the unit can be set up in several positions it also suits cramped laboratory places and changing assembly stations.

COMPATIBILITY AND SCOPE OF DELIVERY

Supplied as the mobile trolley with special blower, flow control, loading indicator and adsorption cassette fitted. Capture elements and hoses are chosen to suit the process, suction nozzles come in 50, 63 and 75 mm. The replacement filter is cassette ULT 02.1.240.