

Alsident 50-57-1-5. **Extraction arm system DN50** **2 joints, 745 mm, white -** **table mounting**

Item no. WL20608

Manufacturer Alsident

Extraction arm system DN50 2 joints, 745 mm, white - table mounting

TECHNICAL DATA

 Colour **White**

 Weight **0.1 kg**


DESCRIPTION

The Alsident 50 system has tubes with a diameter of 50 mm and is suitable for air volumes of 45 -85 m3/h. As a result, the system is ideally suited for use in industries with smaller detection tasks, such as the electronics industry, laboratories, laser technology or even for specialist rooms in schools.

- All components RoHS compliant
- Maintenance-free O-rings
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- Protective grille (accessory) to prevent foreign bodies from being sucked in

PRODUCT DETAILS

item number	WL20608
model	50-57-1-5
manufacturer	ALSIDENT
manufacturer item number	50-57-1-5
order unit	piece

colour	whitely
material	Anodised aluminium tubes - layer thickness 10 µ, polypropylene joints
product series	Alsident System 50 AL
diameter of tube	50 mm
air volume extraction arm	45-85 m³/h
joint colour	white
range	745 mm
number of joints	2
assembling	table mounting
ESD safe	no