

Solder wire lead-free 1 mm 50 g Sn99Ag0.3Cu0.7 - JBC SN5450

Item no. WL21612

Manufacturer JBC

Lead-free SN5450 solder wire with 1 mm diameter on a 50 g reel. The Sn99Ag0.3Cu0.7 alloy suits manual and automated soldering. The reel mounts on the AP130, AP250 and 55N Pulsmatic tin feeders.

TECHNICAL DATA

Weight **0.1 kg**



DESCRIPTION

The lead-free SN5450 solder wire with Sn99Ag0.3Cu0.7 alloy is supplied on a 50 g reel and has a 1 mm diameter. It mounts on the JBC tin feeders AP130, AP250 and 55N Pulsmatic and therefore suits both manual and automated soldering.

BENEFITS

- Lead-free Sn99Ag0.3Cu0.7 alloy
- 1 mm diameter for fine to medium joints
- 50 g reel mounts on AP130, AP250 and 55N Pulsmatic
- Suitable for manual and automated tin feed

TECHNICAL DATA

Item no.	WL21612
Manufacturer item no.	SN5450
Manufacturer	JBC
Model	0002119 / SN5450
Diameter	1 mm
Reel size	50 g
Alloy	Sn99Ag0.3Cu0.7

Dimensions with packaging (LxWxH)

110 mm x 80 mm x 40 mm

Order unit

piece

APPLICATIONS

Lead-free soldering by hand and on automated tin feeders during assembly, repair and rework.

COMPATIBILITY AND SCOPE OF DELIVERY

Mounts on AP130, AP250 and 55N Pulsmatic with tin feed. Supplied as a 50 g reel.