

Soldering tip bevelled, D 3 mm, for T245 iron - JBC C245-912

Item no. WL22522

Manufacturer JBC

C245 series soldering tip for the JBC T245 iron (formerly AD-2245), bevelled geometry with diameter 3 mm. The integrated heater and sensor give fast heat-up and a stable temperature; sleep and hibernation in the stand reduce tip wear.


TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **Spain**

HS-Code **85159080900**

Serie **C245**

Weight **0.1 kg**


STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The C245-912 soldering tip from the JBC C245 series fits onto the T245 iron (formerly AD-2245) and carries the heat straight from the element to the working face. Its bevelled geometry with diameter 3 mm suits general soldering on electronic assemblies.

BENEFITS

- Heater and sensor integrated in the cartridge for fast heat-up and stable temperature.
- Bevelled shape (D 3 mm) for precise heat transfer to the joint.
- Sleep and hibernation when placed in the stand protect the tip and save energy.
- Tool-free tip change on the T245 iron shortens changeover times.
- Total length 100 mm, tip length 8 mm for good reach across the board.

TECHNICAL DATA

Item no.	WL22522
Model	C245-912
Manufacturer	JBC

Manufacturer item no.	C245912
Tip / product series	C245
Tip shape	round
Tip alignment	bevelled
Tip diameter	3 mm
Tip length	8 mm
Total tip length	100 mm
Integrated heater	yes
Compatible iron / handpiece	T245
Order unit	piece
Packaging size (LxWxH)	110 x 12 x 12 mm

APPLICATIONS

Hand and rework soldering of THT and SMD components, repairs and general electronics soldering with the JBC T245 iron.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits the JBC T245 iron (T245-A, T245-PA) and control or soldering stations using the T245 handpiece (e.g. CD-2BQF, CDE-2BQA, DDE). Scope of delivery: one C245-912 soldering tip.

ESD-safe for use to IEC 61340-5-1. Manufacturer JBC, country of origin Spain.