

Guide tube for solder wire 0,6-0,8 mm with hose for AL-2A - JBC 2402

Item no. WL22536

Manufacturer JBC

Guide tube with hose for the automatic solder wire feed on the AL-2A. Designed for solder wire of 0,6-0,8 mm diameter, it ensures jam-free wire delivery to the tip.

TECHNICAL DATA

Country of Manufacture Spain

HS-Code 85159080900

Weight 0.1 kg



DESCRIPTION

The JBC 2402 is a guide tube with hose for the soldering iron with automatic tin feed (AL-2A). It reliably guides solder wire of 0,6-0,8 mm diameter from the feeder to the tip and prevents kinks and jams in continuous operation.

BENEFITS

- Exact fit for 0,6-0,8 mm solder wire: smooth, jam-free feeding.
- Supplied complete with hose, mounts directly on the AL-2A.
- Wear part for quick replacement on wear or wire change.
- Genuine JBC spare part for consistent feed quality.

TECHNICAL DATA

Model	2402
Manufacturer item no.	2402
Item no.	WL22536
Solder wire diameter	0,6-0,8 mm
Scope of delivery	guide tube with hose
Dimensions with packaging (LxWxH)	245 mm x 185 mm x 45 mm
Fits	AL-2A

APPLICATIONS

Replacement and maintenance of the automatic solder wire feed on JBC soldering stations with tin feed, for example when switching to a different wire gauge.

COMPATIBILITY AND SCOPE OF DELIVERY

Fits JBC soldering irons with automatic tin feed (AL-2A) and the matching ALE250 stations (e.g. ALE-210VA). Supplied as a guide tube with hose.

Made in Spain. CE, RoHS.