

Cab 8915701. Metal PCB magazine 701.3, 320x355x563 mm

Item no. WL23099

Manufacturer cab

Metal PCB magazine 701.3, 320x355x563 mm

TECHNICAL DATA

Weight

0.1 kg

DESCRIPTION

PCB magazines series 700: variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

- for high mechanical + thermal stress
- Model: 701.3
- LP: W = 10-250 mm (adjustable), L max = 342 mm
- Magazine: H x W x D = 563 x 320 x 355 mm
- groove depth 3 mm, with transport lock
- Metal web wall
- width adjustment by toothed belt

- stackable (with stacking knobs) or for reversible operation
- Temperature of inserts 200 °C, environment 100 °C

PRODUCT DETAILS

item number	WL23099
model	8915701
manufacturer	CAB
manufacturer item number	8915701
order unit	piece
temperature max.	200 °C
ESD safe	no
Series PCB magazines	Series 700
Material PCB magazine	metal