

Cab 8915703. Metal PCB magazine 703.3, 380x400x563 mm

Item no. WL23101

Manufacturer cab

Metal PCB magazine 703.3, 380x400x563 mm

TECHNICAL DATA

Weight

0.1 kg

DESCRIPTION

PCB magazines series 700: variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by means of a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

- for high mechanical + thermal stress
- Model: 703.3
- LP: W = 10-310 mm (adjustable), L max = 387 mm
- Magazine: H x W x D = 563 x 380 x 400 mm
- groove depth 3 mm, with transport lock
- Metal web wall
- width adjustment by toothed belt

- stackable (with stacking knobs) or for turning operation
- Temperature of inserts 200 °C, environment 100 °C

PRODUCT DETAILS

item number	WL23101
model	8915703
manufacturer	CAB
manufacturer item number	8915703
order unit	piece
temperature max.	200 °C
ESD safe	no
Series PCB magazines	Series 700
Material PCB magazine	metal