

Knipex 70 06 140. Diagonal cutter, chrome-plated, insulated 140 mm

Item no. WL23702

Manufacturer Knipex

Diagonal cutter, chrome-plated, insulated 140 mm

TECHNICAL DATA

Certification	IEC 60900
Norm	DIN ISO 5749
Weight	0.1 kg



STANDARDS & COMPLIANCE

EN 60900 DIN ISO 5749 IEC 60900

DESCRIPTION

OTHER VERSIONS

item number	tether attachment point	tool length
WL23697	nein	160 mm
WL23702	nein	140 mm
WL61645	nein	125 mm
WL61646	ja	160 mm
WL61647	ja	180 mm
WL61648	nein	180 mm

The indispensable side cutter for versatile use. High-quality material and precise workmanship for a long service life. Precision cutting edges for soft and hard wire. Clean cut on thin Cu-wires, also at the cutting tips. Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC. Slim head shape for use in hard-to-reach work areas. with bevel. - Cutting values medium-hard wire (diameter): Ø 2.5mm - Cutting values hard wire (diameter): Ø 1.8mm - Cutting values soft wire

(diameter): Ø 4.0mm - VDE-tested: Yes

- Pliers: chrome-plated
- Handles: insulated with multi-component grips, VDE-tested
- Shape: 0
- High-quality material and precise processing for a long service life
- Precision cutting for soft and hard wire
- Clean cut with thin Cu wires, also at the cutting tips
- cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC
- Slim head shape for use in working areas that are difficult to access
- Vanadium electric steel, forged, multi-stage oil-hardened

PRODUCT DETAILS

item number	WL23702
model	70 06 140
manufacturer	KNIPEX
manufacturer item number	70 06 140
dimensions (LxWxH)	145 mm x 54 mm x 25 mm
dimensions with packaging (LxWxH)	152 mm x 61 mm x 30 mm
Packaging volume	0.27 dm³
order unit	piece
type of packaging	single pack
standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS conform	no
surface	chrome-plated
VDE	no
tether attachment point	nein
ESD safe	no
tool length	140 mm
type of side cutter	side cutter
type of handle	insulated with multi-component sleeves, VDE-tested
cutting value wire diameter hard	1.8 mm
cutting value wire diameter medium	2.5 mm
cutting value wire diameter soft	4 mm