

# Soldering tip SxP chisel 30° 2.5 x 10 mm - Oki SFP-CH25

**Item no.** WL24724 **Manufacturer** Oki

**Manufacturer no.** SFP-CH25

SxP chisel-shaped soldering tip 2.5 x 10 mm for the MFR-H1-SC handpiece of the Oki MFR SmartHeat range. SmartHeat technology holds the tip at a constant 421 °C without separate calibration. Suited to most standard applications.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>United States</b>
Execution	<b>ESD (antistatic)</b>
HS-Code	<b>85159080900</b>
Temperature (max.)	<b>421</b>
Weight	<b>0.1 kg</b>

## STANDARDS & COMPLIANCE

**ESD safe**

## DESCRIPTION

Oki SxP series soldering tip with chisel-shaped geometry (width 2.5 mm, length 10 mm) for the MFR-H1-SC handpiece of the MFR SmartHeat soldering and rework stations. Each tip carries the heater and the SmartHeat sensor that holds the tip at a constant 421 °C with no external calibration.

### Benefits

- Constant 421 °C tip temperature through the integrated SmartHeat control
- Chisel-shaped geometry 2.5 x 10 mm for most standard applications
- Tool-free tip change on the MFR-H1-SC handpiece
- Lead-free soldering, suitable for ESD workplaces

## Technical data

Manufacturer part no.	SFP-CH25
Product series	SxP
tip width	2.5 mm
tip length	10 mm
tip shape	meißelförmig   chisel   en biseau
Tip temperature	421 °C
Compatible handpiece	MFR-H1-SC
Manufacturer	OKI / Metcal

## Applications

General soldering on PCBs and electronic assemblies, through-hole and surface-mount joints, and rework at the ESD bench.

## Compatibility

Fits the MFR-H1-SC handpiece of the Oki MFR SmartHeat range. Supplied as one soldering tip SFP-CH25.

RoHS compliant, lead-free capable, ESD-safe. Manufacturer OKI / Metcal, USA.