

Desoldering tip DxP series long, inner dia 0.79 mm / outer dia 2.05 mm - Oki DFP-CNL3

Item no. WL24761

Manufacturer Oki

DxP series desoldering tip (long) with 0.79 mm inner and 2.05 mm outer diameter, 12.8 mm tip length. Fits the OKI MFR-1150, MFR-1350 and MFR-1351 desoldering systems, working temperature up to 421 °C.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	United States
HS-Code	85159080900
Weight	0.1 kg

Kein Produktbild

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

This OKI DxP series desoldering tip (long version) is designed for the SmartHeat MFR-1150, MFR-1350 and MFR-1351 desoldering systems. The 0.79 mm inner diameter draws solder cleanly from plated through-holes without damaging the pad or trace.

KEY BENEFITS

- 0.79 mm inner diameter for targeted solder removal from through-holes
- 2.05 mm outer diameter and 12.8 mm tip length for good access
- SmartHeat technology holds the tip temperature stable at 421 °C
- Suitable for most standard desoldering applications

TECHNICAL DATA

Manufacturer part no. / MPN	DFP-CNL3
Product series	DxP series (long)

Inner diameter	0.79 mm
Outer diameter	2.05 mm
Tip length	12.8 mm
Tip temperature	421 °C
Sales unit	Piece

APPLICATIONS

Desoldering of leaded components, through-hole (THT) rework and PCB repair in electronics manufacturing, service and laboratory work.

COMPATIBILITY & SCOPE OF DELIVERY

Fits the OKI MFR-1150, MFR-1350 and MFR-1351 desoldering systems. Scope of delivery: 1 desoldering tip.

RoHS compliant, suitable for ESD-safe work. Origin: USA.