

SG-LPT-GR-ABS-148-210X240. ESD air cushioned bag shielding with flap 240x210 mm

Item no. WL24833

Manufacturer Safeguard

ESD air cushioned bag shielding with flap 240x210 mm

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe DIN EN 61340-5-1

DESCRIPTION

SafeGuard's shielding air bubble bag has a 30 mm flap and offers electrostatic and mechanical protection for sensitive components. Of course, it meets the requirements of DIN EN 61340-5-1.

- Surface resistance: $R_{pp} < 1 \times 10^{11} \Omega$
- ESD-STM 11.11 @12% HR
- Discharge time: $< 0.05 \text{ sec.}$ FTMS 101 Mtd 406
- Shielding effect: $< 50 \text{ nJ}$
- material: shielding foil + PE air cushion
- Damper dimensions: 30 mm
- for electrostatic and mechanical protection

PRODUCT DETAILS

item number	WL24833
model	SG-LPT-GR-ABS-148
manufacturer	SAFEGUARD

manufacturer item number	SG-LPT-GR-ABS-148-210X240
length	210 mm
width	240 mm
order unit	piece
colour	grey
property packaging	shielding
film thickness	148 µm