

ESD grounding box with 3 x 10 mm DK and 3 m earthing lead, 1 MΩ each - A1-ESD WL24947

Item no. WL24947 **Manufacturer** A1-ESD

Grounding box with three 10 mm snap connections, each with a 1 MΩ safety resistor for personnel grounding. The 3 m earthing lead connects the workstation to protective earth.

TECHNICAL DATA

Article authenticity	Original product
Colour	Yellow
Condition of article	New
Execution	ESD (antistatic)
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe | IEC 61340-5-13 | IEC 61340-5-1

DESCRIPTION

The grounding box WL24947 bundles three 10 mm snap connections for personnel grounding at one central point. The 3 m earthing lead connects the ESD workstation to protective earth; each connection has a 1 MΩ safety resistor.

Benefits

- Three 10 mm snap connections for wrist straps and mats
- 1 MΩ safety resistor per connection to IEC 61340-5-1
- 3 m earthing lead for connection to protective earth
- For personnel grounding at the ESD workstation

Technical data

- Model: 30-560-0039
- Connection: 3 x DK 10 mm snap
- Resistance: 1 MΩ safety resistor per connection
- Cable length: 3 m
- Colour: yellow
- Selling unit: 1 piece

Application

Personnel grounding at ESD workstations with several wrist straps or mats.

Standards and compliance

Supports the IEC 61340-5-1 requirements for grounding within the EPA.