

# ESD earthing point with 3 x 4 mm banana sockets and 3 m lead, 1 M $\Omega$ each, yellow - A1-ESD WL24950

**Item no.** WL24950 **Manufacturer** A1-ESD

Earthing point for mounting under the table top with three 4 mm banana sockets, each with a 1 M $\Omega$  safety resistor. The 3 m earthing lead is used for personnel grounding.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Colour	<b>Yellow</b>
Condition of article	<b>New</b>
Execution	<b>ESD (antistatic)</b>
Norm	<b>IEC 61340-5-1</b>
Sales unit	<b>1 Stück</b>
Weight	<b>0.1 kg</b>



## STANDARDS & COMPLIANCE

**ESD safe** IEC 61340-5-1

## DESCRIPTION

The earthing point WL24950 mounts under the table top and provides three 4 mm banana sockets for personnel grounding. Each connection has a 1 M $\Omega$  safety resistor; the 3 m earthing lead connects the workstation to protective earth.

## Benefits

- Three 4 mm banana sockets for wrist straps and mats
- 1 M $\Omega$  safety resistor per connection to IEC 61340-5-1
- For space-saving mounting under the table top
- 3 m earthing lead for connection to protective earth

## Technical data

- Model: 30-551-3040
- Connection: 3 x 4 mm banana socket
- Resistance: 1 MΩ safety resistor per connection
- Cable length: 3 m
- Colour: yellow
- Selling unit: 1 piece

## Application

Personnel grounding at ESD workstations where the ground point sits hidden under the table top.

## Standards and compliance

Supports the IEC 61340-5-1 requirements for grounding within the EPA.