

Knipex 79 22 125 ESD. ESD precision electronics side cutter, ro with, 125 mm

Item no. WL24972

Manufacturer Knipex

ESD precision electronics side cutter, round, 125 mm

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Weight **0.1 kg**

STANDARDS & COMPLIANCE

ESD safe EN 61 340-5 DIN ISO 9654

DESCRIPTION

ESD precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components; also without facet for flush cutting. Precision cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Approx. 20 % less weight than conventional electronic pliers. Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range. Smooth-running double spring for smooth and even opening. Ergonomically optimised multi-component handles. round head. - Shape: 2 - Cutting values medium hard wire (diameter): Ø 1.0mm - Cutting values soft wire (diameter): Ø 0.1 - 1.7mm - Jaw length (B): 10mm - Jaw thickness (at joint) (D): 6.5mm - Head width (A): 11mm - ESD: Yes

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components
- Also without facet for flush cutting
- Precision cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Approx. 20 % less weight than conventional electronic pliers

- Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range
- Smooth-running double spring for smooth and even opening
- Ergonomically optimised multi-component sleeves

PRODUCT DETAILS

item number	WL24972
model	79 22 125 ESD
manufacturer	KNIPEX
manufacturer item number	79 22 125 ESD
dimensions (LxWxH)	115 mm x 61 mm x 18 mm
dimensions with packaging (LxWxH)	189 mm x 72 mm x 48 mm
Packaging volume	0.637 dm ³
order unit	piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
RoHS conform	no
surface	burnished
VDE	no
ESD safe	yes
Cut form	without bevel
tool length	125 mm
type of side cutter	side cutter
type of handle	with multi-component sleeves
cutting value wire diameter medium	1 mm
cutting value wire diameter soft	1.7 mm