

Alsident 75-6555-1-5. Extraction arm system DN75, 3 joints, 1290 mm, white - table mounting

Item no. WL25795

Manufacturer Alsident

Extraction arm system DN75, 3 joints, 1290 mm, white - table mounting

TECHNICAL DATA

Colour **White**

Weight **0.1 kg**



DESCRIPTION

Alsident's DN75 system can be used in a wide range of applications, including laboratories, laser technology, chemical and pharmaceutical industries, as well as school classrooms. The tubes have a diameter of 75 mm and the recommended air volume is 80 m³/h to 180 m³/h.

- Maintenance-free O-rings
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- Protective grille (accessory) to prevent foreign bodies from being sucked in
- All components RoHS compliant

PRODUCT DETAILS

item number	WL25795
model	75-6555-1-5
manufacturer	ALSIDENT
manufacturer item number	75-6555-1-5
order unit	piece

colour	whitely
material	Anodised aluminium tubes - layer thickness 10μ, joints made of impact-resistant, chemically resistant polypropylene (PP)
product series	Alsident System 75 AL
diameter of tube	75 mm
air volume extraction arm	80–180 m³/h
joint colour	white
range	1290 mm
number of joints	3
assembling	table mounting
ESD safe	no