

## Alsident 50-3721-1-23-050. Extraction arm System 50 Flex 2 joints, 900 mm, black - table mounting

Item no. WL25902

Manufacturer Alsident

Extraction arm System 50 Flex 2 joints, 900 mm, black - table mounting

### TECHNICAL DATA

|        |        |
|--------|--------|
| Colour | Black  |
| Weight | 0.1 kg |



### DESCRIPTION

The Alsident System 50 Flex is intended for an air volume of 45 - 85 m<sup>3</sup>/h and has a pipe diameter of 50 mm. The Flex system is particularly suitable for the electronics industry and laboratories.

- Increased possibilities of positioning due to the flexible hose
- Suction tip with an elaborately processed cantilever to increase the efficiency of detection
- Maintenance-free O-rings
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- All components RoHS compliant.

### PRODUCT DETAILS

|                          |                  |
|--------------------------|------------------|
| item number              | WL25902          |
| model                    | 50-3721-1-23-050 |
| manufacturer             | ALSIDENT         |
| manufacturer item number | 50-3721-1-23-050 |
| order unit               | piece            |

|                           |                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------|
| colour                    | black                                                                                                      |
| material                  | Tubes and suction tip made of anodised aluminium - layer thickness 10μ, plastic hose, polypropylene joints |
| product series            | Alsident System 50 AL                                                                                      |
| joint colour              | black                                                                                                      |
| diameter of tube          | 50 mm                                                                                                      |
| number of joints          | 2                                                                                                          |
| range                     | 900 mm                                                                                                     |
| assembling                | table mounting                                                                                             |
| air volume extraction arm | 45-85 m³/h                                                                                                 |
| ESD safe                  | no                                                                                                         |