

ESD earthing box 3x10 mm stud, angled, yellow - Warmbier WL25939

Item no. WL25939

Manufacturer Warmbier

Angled earth bonding point (EBP) with three 10 mm studs, each with a 1 MΩ safety resistor. The angled body improves access at the table edge, includes a 2 m earthing lead.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Yellow
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Warmbier earthing box 2200.W.3 is a fixed earth bonding point (EBP) in an angled design. The inclined connection face makes it easier to attach and remove the studs at the table edge.

BENEFITS

- Angled body for convenient access at the workstation
- Three 10 mm studs for multiple simultaneous connections
- One 1 MΩ safety resistor per connection to protect the operator

TECHNICAL DATA

- Connections: 3 x 10 mm stud
- Resistance: 1 MΩ safety resistor per connection
- Earthing lead: 2 m, 4 mm eyelet termination
- Design: angled
- Colour: yellow
- Manufacturer part no.: 2200.W.3

APPLICATIONS

For ESD workstations where the grounding points should sit within easy reach at the table edge.

STANDARDS AND COMPLIANCE

Supports an EPA built to IEC 61340-5-1.