

OKI HCT-1000. Programmable handheld hot air station, with HCT-HV1 100-240 V

Item no. WL26061

Manufacturer Oki

Programmable handheld hot air station, with HCT-HV1 100-240 V

TECHNICAL DATA

Power	600 W
Temperature (max.)	bis 450 °C
Temperature range	100-450 °C
Weight	0.1 kg



DESCRIPTION

- fully programmable
- can both remove and place SMT components
- has digital controls, an internal or external thermocouple feedback, a program memory of up to 50 profiles and an integrated vacuum holder for placement and removal of components
- manual mode for quick setup
- External thermocouple for process design and verification
- Handpiece control for heating and vacuum
- various operating modes: manual, 4-zone heating (with the system MRS-1100A)
- The HCT-1000 is connected to the PCT-1000 via a cable when used as part of the MRS system.
- can be used with the adjustable tool holder ATH-1100A

PRODUCT DETAILS

item number	WL26061
model	HCT-1000
manufacturer	OKI
manufacturer item number	HCT-1000
scope of supply	HCT-PS1000 power supply unit HCT-HV1 Handpiece HN-J0005 Nozzle HNA-1 nozzle adapter

order unit	piece
frequency	50/60 Hz
nominal power	600 W
voltage	100-240 V
vacuum	15" Hg (381mm Hg)
temperature range °C (to)	450 °C
Air Flow	5-25 LPM