

Waldmann
112980000-00551364.
System luminaire TAMETO -
SAHQ 88 R, mounting
top/fixed, dimmable, 4000 K

Item no. WL28559

Manufacturer Waldmann

System luminaire TAMETO - SAHQ 88 R, mounting top/fixed,
dimmable, 4000 K

TECHNICAL DATA

Weight

0.1 kg**DESCRIPTION**

The Tameto system luminaire from Waldmann is convincing on many levels: Maintenance-free LED technology, extremely homogeneous, glare-free and flicker-free light as well as light emission with a cone prism structure for perfect glare control. The Tameto system luminaire is available in various lengths for different desk widths and lighting requirements to equip the perfect industrial workplace. The robust aluminium housing and enclosed design protect the inside of the system luminaire and work surface from contamination.

- Control gear: Electronic ballast
- Connected loads: 220-240 V, 50/60 Hz
- Luminous flux: 2900 lm
- Luminaire light yield: approx. 87 lm/W
- Light colour: neutral white
- Colour rendering (Ra): >80
- glare control: conical prismatic diaphragm
- Technique: infinitely dimmable
- Operation: Rocker switch
- Mains connection cable: approx. 3 m; mains plug CEE 7/VII
- Mounting: screw-on tab
- Length: 1256 mm
- Em: 1071 lx, Emax: 1448 lx, Emin: 659 lx

PRODUCT DETAILS

item number	WL28559
model	SAHQ 88 R
manufacturer	WALDMANN
manufacturer item number	112980000-00551364
length	1300 mm
width	220 mm
depth	120 mm
order unit	piece
Lamp or magnifier type	workplace light
luminous flux	2900 lm
connections	220-240 V; 50/60 Hz
colour temperature	4000 °K
power	33 W
equipping	LED, energy efficiency class A+
attachment	Ceiling mounting
housing colour	Aluminium/plastic, anodised, aluminium coloured (colourless anodised)
protection class	1
protection class	20 IP
ESD safe	no