

Metcal MX-5250. Two-channel Desoldering station with Desoldering gun MX-DS1

Item no. WL28582

Manufacturer Metcal

Two-channel desoldering station with desoldering gun MX-DS1

TECHNICAL DATA

Power	80 W
Temperature (max.)	bis 450 °C
Temperature range	330-450 °C
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

- for desoldering components with plated through-hole
- non-slip handle
- "shop-air" hand tool in combination with the new dual-simultaneous supply offers unprecedented heat output
- can operate two handpieces, which dynamically share the 80 Watt output power as required
- Better process control with SmartHeat technology
- ESD safe
- Built-in power meter with digital display and bar graph that dynamically provides the operator with feedback on the status of the soldering process.
- Metcal TipSaver Workstand improves tip life with Auto-Sleep feature

PRODUCT DETAILS

item number	WL28582
model	MX-5250
manufacturer	METCAL
manufacturer item number	MX-5250

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

scope of supply	MX-PS5200: power supply, 100 to 240 VAC input, dual switch port with LCD display MX-DS1: Desoldering gun handpiece with one cartridge removal pad MX-W5DS: Work stand for desoldering gun handpiece with one sponge and one brass cushion AC-CB1: Desoldering chamber cleaning brush AC-CB2: Pipe cleaning brush MX-DCF1: Chamber lining and filter package AC-TC: Desoldering tip cleaner MX-RM8E: Desoldering cable MX-DAH4: ESD air hose with fitting
order unit	piece
station type	desoldering station