

Separating underlay for ESD floor covering, roll 2.0 m x 35 m, vapour-tight - Warmbier WL31877

Item no. WL31877

Manufacturer Warmbier

Dimensionally stable, vapour-tight separating underlay for the loose laying of ESD floor coverings on difficult substrates. The roll is 2.0 m wide, 35 m long and 1.3 mm thick.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Sales unit	Rolle 35 m
Weight	0.1 kg
Width	2000



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Warmbier separating underlay enables loose laying of ESD floor coverings in an EPA and their later residue-free removal. It is dimensionally stable, vapour-tight and ready to cover immediately on difficult substrates.

BENEFITS

- Dimensionally stable, vapour-tight separating underlay for loose laying
- Ready to cover immediately on difficult substrates
- Ventilation and de-aeration function
- For medium mechanical stress

TECHNICAL DATA

- Model: 1280.TF201
- Width: 2000 mm (2.0 m)
- Length: 35 m
- Material thickness: 1.3 mm
- Selling unit: roll

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

APPLICATIONS

Decoupling and laying of ESD floor coverings on difficult substrates in EPA protected areas.